## FM33/43G-FM43D5

SINGLE DISC MACHINES





A range of single disc machines for the cleaning and treatment of any type of hard floors



FM33/43G-FM43DS

FM33 is particularly suitable for heavy duty works. The brush head unit is made of steel and combines high motor power with compact size, to guarantee an excellent finishing also in small

FM43 G is a single disc machine robust and easy to maintain. With a stainless steel frame and PPL coating, it combines efficiency and versatility together with a modern ergonomics.

Each machine can be equipped with a 7 Kg extra weight, upon request. Moreover the removable power cable makes transport and maintenance easier.

## FM33/43 G

They are equipped with a new nylon gear box for long life, high reliability and quiet operation.

- They are suitable for:
- Water scrubbing of hard and vinyl floors
- Foam or powder carpet cleaning
- Dry maintenance: stripping and polishing of vinyl floors

FM43 DS is a dual speed belt driven single disc machine, cable powered, with large tank capacity and 43 cm working width. It is extremely low-noise and suitable for:

scrubbing, maintenance cleaning and polishing synthetic, vinyl and carpet floors.



FM33/43 G - FM43 DS

TECHNICAL DATA		FM33/43 G	FM43 DS	
Drive		Nylon gearbox drive	Belt	
Working width	cm	33/43	43	
Brush Ø	cm	33/43	43	
Disc brush rotations	rpm	160	180/400	
Power supply	V/Hz	230/50	230/50	

TECHNICAL DATA		FM33/43 G	FM43 DS	
Tank	1	15	15	
Pad holder	cm	33/43	43	
Power	W	1100	1100/1350	
Machine dimensions (L x h x w) mm		515x1160x444/	565x1160x450	
		565x1160x450		

CERTIFICATIONS





FIMAP spa – Via Invalidi del Lavoro, 1 – 37059 S. Maria di Zevio – Verona – Italy Tel. +39 045 6060411 - Fax +39 045 6060417 - E-mail: fimap@fimap.com



00800-05070000

Scan the QR Code with your Smart Phone and visit our web-site



ves the right, at anytime, to

images are shown as reference only and are not binding as to the actual design and/or equipment – Copyright  $^{\odot}$ 

Fimap 2015 - COD. 302197 - AA - 12/201



They are equipped with a safety system through which the machine activation

INICAL DATA		FM33/43 G	FM43 DS	ΤI
		Nylon gearbox drive	Belt	Ta
king width	cm	33/43	43	Pa
n Ø	cm	33/43	43	Pc
brush rotations	rpm	160	180/400	N
r supply	V/Hz	230/50	230/50	